

Aquilon RS4

Ref. AQL-RS4



Mission-critical 4K/8K multi-screen presentation system and videowall processor with 24 inputs and 16 outputs, delivering uncompromising presentation experiences to high-end staging and premium system integration



Outstanding Performances

Like all the products of the **LivePremier™** series, **Aquilon RS4** offers versatile 4K digital connectivity, unmatched real-time 10/12-bit 4:4:4 video processing power, best-in-class image quality and pure 4K60p on each input and output with ultra-low latency. Ideally tailored to large scale auditoriums, conference rooms, staging live events, houses of worships, corporate lobbies and sports venues, **Aquilon RS4** offers almost unlimited possibilities for future applications and possesses enough bandwidth to support evolving requirements, such as 8K and higher framerates.

Industrial Grade Reliability

Aquilon RS4 was specifically engineered to perform to the highest standards in mission-critical applications and road-hardened to survive frequent shipping and tough live events. By combining a heavy-duty modular design, the highest quality components selected for their proven reliability, and features such as redundant hot swappable power supplies and smart thermal management, **Aquilon RS4** delivers uninterrupted 24/7 performance and peace of mind!

Versatile for the Highest Flexibility of Configurations

Aquilon RS4's modular design allows you to easily swap I/O cards to accommodate a variety of connectivity arrangements and your match source and display requirements. **Aquilon RS4** offers 24 seamless inputs, 16 outputs configurable as single screens, edge-blended widescreens or scaled auxiliary outputs, 2 dedicated Multiviewer outputs, up to 24x 4K or 48x HD freely assignable layers, as well as powerful features that will allow you to handle any creative display configuration, such as a custom output formats, output rotation, AOI, bezel compensation and pixel pitch management...

Smart Functionalities

Aquilon RS4 features state-of-the-art real time processing features that will help you to unleash all your creative potential and produce flawless, stunning shows: true seamless switching, flying layer movement, advanced cut and fill, cutting edge keying engine... **Aquilon RS4** also allows to remove external audio de-embedding boxes: In just a few easy clicks, audio can be de-embedded from video sources, routed directly using onboard Dante™ card and re-embedded from external audio processor for sending to display, recording device, or streaming.

Best User Experience

Entirely re-imagined, the new web-based user interface is intuitive, simple, state-of-the-art and offer dozens of features you will love instantly and that make configuration and control a breeze.

24 inputs	16 outputs	4K60 4:4:4 10-12 bit	2 multi- viewers	HDR compliant		HDMI 2.0	DP 1.2	12G-SDI	HDCP 2.2
---------------------	----------------------	-----------------------------------	-------------------------------	-------------------------	--	--------------------	---------------	----------------	--------------------

- Aquilon RS4 at a glance**
- ▶ Industrial grade reliability
 - ▶ 24x 4K60p inputs and 16x 4K60p outputs - field swappable I/O cards
 - ▶ Versatile 4K digital connectivity: HDMI2.0, DP1.2, 12G-SDI
 - ▶ Real-time 10/12-bit 4:4:4 video processing
 - ▶ 120 Megapixels throughput on Program at 10 bits 4:4:4 @60Hz
 - ▶ Up to 24x 4K60p or 48x DL/2K60p single layers (+live backgrounds)
 - ▶ HDR compliant with HDR10 and HLG
 - ▶ Intuitive HTML5-based user interface with live source thumbnails
 - ▶ Native DANTE audio networking hardware and support
 - ▶ Future proof modular design to support to 8K and 120 fps...

Aquilon Models	RS1	RS2	RS3	RS4	C	C+
4K60p inputs	16	16	24	24	up to 16	up to 24
4K60p outputs	8	12	12	16	up to 16	up to 20
Max 4K60p single layers	8	16	16	24	up to 16	up to 24
Max DL/2K60p single layers	16	32	32	48	up to 32	up to 48
Simul. 4K still image channels	12	12	24	24	up to 12	up to 24
Build-to-Order (BTO)					✓	✓
Rack units	4	4	5	5	4	5

Key Features

Based on LivePremier™ platform

Highly ruggedized chassis with cleanable air filter

Hot-swappable redundant power supplies

24x seamless 4K60p inputs (12x HDMI 2.0, 8x DP 1.2, 4x 12G-SDI)

16x 4K60p outputs (16x HDMI 2.0)

True 4K60p 10bit 4:4:4 performance on every I/O channel

Field swappable I/O cards to accommodate a variety of connectivity arrangements

Support 4K60p input and output as single, double or quad plugs

120 Megapixels throughput at 10 bits 4:4:4 on Program, without restricting Preview or Multiviewer

Up to 12x 4K60p or 24x Dual/2K60p mixing layers (up to 24x 4K60p or 48x Dual/2K60p single layers)

24x 4K or 48x 2K concurrent still images

Unscaled seamless background mixer on each output (using instantaneous still images or live sources)

Flexible layer management

Seamless crossfade on all mixing layers, on all 24 sources

Scaled 4K60p AUX feature for all non-PGM outputs

Ultra-low latency 10 and 12-bit processing

Ability to place the outputs anywhere on an almost limitless video canvas space for special LED wall applications

Advanced pixel pitch management for LED wall applications

2x configurable 4K Multiviewer outputs with 24x resizable widgets on each, including clocks, countdown and timers

HDR compliant with HDR10 and HLG

Native Dante™ audio networking hardware and support (64x64)

Rotation capability on each output; manage portrait displays

Independent output rates

Framelock or internal sync. generator

Web RCS: highly intuitive, lightning fast web-based user interface based on HTML5

Live video thumbnails shown on GUI

Multi operator real-time collaboration

Password protection and user privileges

Easily create and recall preset looks on all your screens and auxiliary outputs

Custom output formats for non-standard display applications

Area of Interest feature to customize active areas of outputs

Still images support variable alpha-channels for transparent background on logos

Cut and Fill (using two sources or a source and a still image)

Fully functional simulator for offline configuration and practice

EDID management on every input and output

Compliant with HDCP 2.2 and 1.4

Future proof modular design to support to 8K and HFR

Quiet: 49dB average noise at 1m when ambient temperature is less than 32°C/90°F



Remote services and maintenance

Backup and restore functions

Web RCS: Unrivalled Ease of Use


For the best ease of setup and to ensure flawless control of multi-screen presentations, the **LivePremier™** series features a totally new, cutting-edge HTML5-based user interface, the **Web RCS**, compatible with any device or platform including iOS and Android devices.

Conceived to greatly increase productivity and reduce learning curve, the **Web RCS** offers dozens of unique features that simplify configuring and operating, such as live program/preview workspaces with high-resolution dynamic thumbnails of connected sources, multi-operator collaboration with password protection and user privileges, walkthrough guides, keyword search, multi-language support and much more...



The Web RCS is compatible with any device or platform, including iOS and Android devices

Aquilon RS4 can drive three 8K60p LED walls and 4x 4K60p AUX outputs



Technical Specifications

INPUTS

24 seamless 4K60p inputs via 6 field swappable input cards:

12x HDMI 2.0 (up to 4K60p 8 bits 4:4:4 or up to 2560x1440@60p 10 bits 4:4:4)

8x DisplayPort 1.2 (up to 4K60p 10 bits 4:4:4)

4x 12G-SDI (up to 4K60p 10 bits 4:2:2) - compatible with 3G-SDI and 6G-SDI

Support 4K60p input as single, double or quad plugs

Support custom input formats such as 8192x1080@60p or 1080x8192@60p (aka "8k x 1k") on a single connector

Connector status LEDs for easy troubleshooting

OUTPUTS

16 active 4K60p outputs via 4 field swappable output cards:

16x HDMI 2.0 (up to 4K60p 8 bits 4:4:4 or up to 2560x1440@60p 10 bits 4:4:4)

Support 4K60p output as single, double or quad plugs

Support custom output formats such as 8192x1080@60p or 1080x8192@60p (aka "8k x 1k") on a single connector

Connector status LEDs for easy troubleshooting

MULTIVIEWER OUTPUTS

2 dedicated HDMI 2.0 outputs configurable as up to 2x 4K30p or up to 2x 2560x1440@60p or 1x 4K60p

24 resizable widgets on each output

Customizable layouts with 50 memories

Monitor inputs, still images and screens (Program and Preview)

Built-in clocks, countdown and timers

LAYERS & BACKGROUND

Supports mixing layers (true seamless transitions) and single layers (cut transitions)

12x 4K60p or 24x Dual/2K60p mixing layers per system (doubled if single layers)

Layer source can be a live input, a still image or a screen

Each output has an unscaled background mixer supporting seamless transitions - background source can be still image or live source

SCREENS

Outputs configurable as single screens or edge-blended widescreens

16 Program outputs configurable for up to 16x Dual/2K60p or up to 12x 4K60p + 4 auxiliary outputs

Ability to place the outputs anywhere on an almost limitless video canvas space for special LED wall applications

Flexible layer management: each screen gets dedicated layers of various sizes (2K, 4K, ...) using common-pool layer resources

1000 user definable screen presets and 500 master presets

SCALED AUX OUTPUTS

Any unused output configurable as a scaled auxiliary output

Up to 16x 4K60p scaled auxiliary outputs

Can display any input or screen (1:1 or scaled)

HDCP

Compatible with HDCP 1.4 and 2.2

AUDIO

Audio embedding/de-embedding on every input & output (raw audio)

De-embed audio from sources and route directly using onboard DANTE 64x64 card

Re-embed audio from external audio processor for sending to display

PROCESSING

Based on Analog Way exclusive 5th generation scaling engine

Extremely low latency, as low as 1 frame in proper configuration

Motion compensation deinterlacing

BT.601; BT.709; BT.2020; BT.2100 color spaces

Advanced pixel pitch management & bezel compensation

Compliant with HDR

TRANSITIONS & EFFECTS

True A/B Mix

Misc. layer border effects/colors and separate shadow

Transitions: Cut, Fade, Slide, Wipe, Circle, Stretch, Depth, Flying layer movement with programmable paths

Layer effects: Background Cut, Transparency, Luma/Chroma Key, DSK, H&V Flip, Cut and Fill

Colors effects: B&W, Negative, Sepia and Solarize

STILL IMAGES

24x 4K or 48x 2K concurrent still images - fully resizable

Still images support alpha-channel

Still image library with 100 memories

Multi-file download/upload via Web RCS

Capture from live inputs

CONTROL

Web RCS: On-board intuitive web-based user interface

Shot Box²/Control Box²: Cost effective control solutions

New controller scheduled for end 2019

Simple REST API (HTTP & TCP)

Advanced TCP protocol based on JSON

AMX/Crestron drivers

AW VideoCompositor: Premium drag & drop Crestron® GUI

OTHER FEATURES

Tally/GPI-O

Dedicated BNC with loop out for Framelock, blackburst and tri-level sync

Fully functional simulator for offline configuration and practice

EXPANDABILITY

Expansion via simple linking possible (future hardware upgrade)

Dimension (in Rack Units - RU)

▶ 5RU

Dimensions (without rack ears & rack mount)

▶ W 17.28" x H 8.7" x D 28.03"

▶ L 439.8 mm x H 221.2 mm x P 712.5 mm

Dimensions (with handles)

▶ W 18.89" x H 8.7" x D 28.03"

▶ L 482.4 mm x H 221.2 mm x P 712.5 mm

Weight without accessories

▶ 37.3 kg / 81.57 lbs

Operating conditions

▶ Temperature: 0 to 40°C (32 to 104°F)

▶ Humidity: 10% to 80%, non-condensing

Warranty

3-year warranty on parts and labor back to factory

Safety Compliance

▶ IEC/UL/EN 62368-1, CSA22.2 #62368-1

Supplied with

▶ 3x Power supply cord

▶ 1x Web-based Remote Control

Software

▶ 1x Rackmount kit

▶ 1x Ethernet cross cable

▶ 3x MCO 5 pin connectors

▶ 1x User manual (PDF)*

▶ 1x Quick start guide including safety instructions*

 Specifications subject to change without prior notice

AQL-RS4_EN-01/30/2019