



The DF4 is the entry-level motor controller of the EXE line, supplied in flight case. It operate in DIRECT Mode.

Description	Specification
Code	XC DF4
Number of channels	4
Control	Direct (400 – 415 V; 3 ph; 50 Hz)
Input power	1 x CEE 32 A – 5p plug
Output power	4 x CEE 16 A – 4p plug
Protections	- Earth Break switch for power and control - Emergency STOP mushroom - Emergency Choke Coil
Remote	No
Housing	19" 7U rack flight case
Functional Description	<ol style="list-style-type: none"> 1 – Connect the 32A 3 phase plug to the power supply 2 – Connect plugs to for the electric hoists concerned, to the appropriate sockets of the 16A 3 phase 4p 3 – Check that emergency STOP mushroom is not engaged 4 – Arm the Emergency Choke Coil 5 – Arm the Magneto Thermal switch 6 – Check that all 3 warning lights are illuminated 7 – Engage the gear lever corresponding to each motor, to the position required: UP, lever in left position, DOWN, lever in right position. 8 - Pushing the GO button will activate the motors to move simultaneously 9 – Releasing the GO button will cease the movement of the motors, simultaneously
Date of issue 16/03/2005	LITEC s.r.l. – Via Venier, 52 – 30020 Marcon (VE) www.litectruss.com - info@litectruss.com
	LLTCST73GB1 Version 2